

# HD SERIES CART/SKID



PRESSURE WASHERS / SINCE 1970

## FEATURES

1.9 to 3.5 GPM @ 1000 to 2000 PSI



COLD WATER

ELECTRIC

DIRECT DRIVE

**THE RIGHT CHOICE  
FOR TOUGH, COLD-WATER  
CLEANING**

A **36-ft electrical safety cord** with Ground Fault Circuit Interrupter (GFCI)

Durable weld free, corrosion resistant **aluminum frame**

Puncture proof, **flat-free tires** make for easy maneuvering on any terrain, ideal for sites riddled with nails and debris

Easily converts from a **cart to skid**

Durable pressure trapping **unloader** diverts water flow when trigger gun is not activated

**Thermal pump protector** to prevent excessive heat build-up for added safety

Quick-couple **detergent injection** allows for easy application of soap

**50 ft. wire-braided hose** includes guards, couplers and swivels at both ends

Fatigue-free spring-loaded **trigger gun** with spray wand and side handle making for easy point-and-shoot cleaning action

Water resistant **electrical box** for added safety and easy servicing

**Four quick-couple nozzles** made of hardened stainless steel and color-coded for easy spray pattern selection: 15°, 25° & 40° and a detergent nozzle

The **reliable Hotsy direct-drive pump** carries a 7-year limited warranty...best in the industry! Downstream detergent injection allows for easy application of soap



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	MOTOR RPM	AMPS	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HD 1.9/13 Ed	9.801-798.0	1.9	1300	2	120/1	1725	20	LFP2030S	35"x21"x24"	196
HD 2.0/10 Ed	9.801-797.0	2.0	1000	1.5	120/1	1725	15	LFP2030S	35"x21"x24"	212
HD 3.0/10 Ed	9.801-799.0	3.0	1000	2	120/1	1725	20	LF2830S	35"x21"x24"	219
HD 3.5/20 Ea	9.801-800.0	3.5	2000	5	230/1	3450	22	LF3530F	35"x21"x24"	220

**HOTSY.COM**

**NOTE:** We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +\_10% and in some cases are tighter within +\_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2021 Kärcher North America  
P/N HOT\_CWC Effective 06/21

Distributed by: